



(c) NOTES:

1. METALSHELLS: COPPER ALLOY;  
min. 315µin TIN over 40-80µin NICKEL
2. INSULATOR: TPE
3. CLAMPS: STAINLESS STEEL
4. SCREW: STAINLESS STEEL

(d) 5. CONNECTOR IS PART MARKED: PART NO. CONEC ABC

No. of pos.	A <sub>-0,76</sub>	B <sub>+0,25</sub>	C	D <sub>-0,3</sub>	(d) E <sub>+25</sub>	(d) F <sub>-0,76</sub>	Part No.: Bulk package	Part No.: (e) Single package
9	31,19	16,79	25,00 <sup>+0,12</sup> <sub>-0,10</sub>	6,12	8,23	12,93	165X14719X	165X14719XE
15	39,52	25,12	33,30 <sup>+0,15</sup>	6,12	8,23	12,93	165X14729X	165X14729XE
25	53,42	38,84	47,04 <sup>+0,13</sup>	5,99	8,23	12,93	165X14739X	165X14739XE
37	69,70	55,30	63,50 <sup>+0,13</sup> <sub>-0,11</sub>	5,99	8,23	12,93	165X14749X	165X14749XE
50	67,31	52,68	61,10 <sup>+0,14</sup> <sub>-0,11</sub>	5,99	10,95	15,75	165X14759X	165X14759XE

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

				tolerance		dim. in mm	
				date	name		
				drawn	10.09.01	E.Mickenbecker	
1 x e	Ä4033	30.06.2011	K.H.	appd.	10.09.01	A.Mickenbecker	
3 x d	Ä3662	23.08.2010	K.H.	norm	DIN 41652		
1 x c	Ä1912	06.04.2004	Lehmen	d-old			
3 x b	Ä1788	06.06.2004	Lehmen				
a	Origin			<b>CONEC</b> ®			
rev.	description	date	name				

scale:	2:1	
material:	SEE NOTES	
title:	<b>HOOD 9 - 50pos.</b> FOR SOCKET CONNECTOR water resiatant, shielded for EMI/RFI	
dwg no:	Inventor 10	DIN-A4
	16K1A291A	sh: 1
part no:	SEE TABLE	