



Article Number: 170-03102

Plenum Rated Expandable Braided Sleeving (Halar), .375"Dia., Black, 125.0 ft/reel Description:

Base Data		
	Local Order Number	170-03102
	Туре	BSHLR380
	Color	Black (BK)
	Features and Benefits	 Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications. Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation. Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.
	Quantity Per	reel
	Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
	Short Description	Plenum Rated Expandable Braided Sleeving (Halar), .375"Dia., Black, 125.0 ft/reel
Product Dimensions		
	Length L (Imperial)	125.0ft
	Length L (Metric)	38.1m
	Reel Length (imperial)	125.0ft
	Bundle Diameter Min. (Imperial)	0.187"
	Bundle Diameter Min. (Metric)	4.7mm
	Bundle Diameter Max. (Imperial)	0.63"
	Bundle Diameter Max. (Metric)	16.0mm
	Nominal Diameter (Imperial)	3/8"
	Nominal Diameter (Metric)	9.5mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66E/CTFE)
	Material Shortcut	PA66E/CTFE
	Flammability	FAR 25

generated on: 4/7/2017

170-03102



Material and Specifications	Operating Temperature	-103°F to +302°F (-75°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL2024
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	125.0ft
	Package Quantity (Metric)	125.0ft
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	1.08lbs
	Weight (Metric)	0.49kg

generated on: 4/7/2017