## **HellermannTyton**

Article Number: 173-00400

ei. 175-0040

Description:

Electromagnetic Protection Braided Sleeving, 4 mm Dia., PET;TNCU, TCBK, 328.0 ft/Reel

## HellermannTyton

Base Data		
	Local Order Number	173-00400
	Туре	HEGEMIP04
	Color	Tin-coloured and Black (TCBK)
	Features and Benefits	Unique blend of polyester and tin plated copper fibers offers electromagnetic protection as well as secure cable bundling
	Quantity Per	metre
	Product Description	Made of tin-plated copper and polyester threads, Helagaine HEGEMIP braided sleeving offers electromagnetic protection as well as secure cable bundling. The patented material mix offers very good inside and outside abrasion resistance. Also it makes the sleeve expandable and easy to apply. In contrast to purely copper braids, the HEGEMIP sleeve can be bent and twisted and still return to their original form to protect the cable perfectly. The copper wires are protected by the polyester yarn. Therefore breaks and fractures of the metal are prevented, even by bending the sleeve at a 90°-angle. As a result, HEGEMIP braided sleeving is particularly suitable for applications where there is movement and restricted space The inner tube makes insertion of cables easier and protects the sleeves from deformation during transportation.
	Short Description	Electromagnetic Protection Braided Sleeving, 4 mm Dia., PET;TNCU, TCBK, 328.0 ft/Reel
Product Dimensions		
	Length L (Imperial)	328.0ft
	Length L (Metric)	100.0m
	Reel Length (imperial)	328.0ft
	Bundle Diameter Min. (Imperial)	0.16"
	Bundle Diameter Min. (Metric)	4mm
	Bundle Diameter Max. (Imperial)	0.26"
	Bundle Diameter Max. (Metric)	6mm
	Diameter D (imperial)	0.16"
	Diameter D (metric)	4mm
	Nominal Diameter (Imperial)	5/32"
	Nominal Diameter (Metric)	4mm

## 173-00400

## **HellermannTyton**

Material	Polyester, halogen free (PET)
Material Shortcut	PET
Flammability	UL 94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
REACH Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	328.0ft
Package Quantity (Metric)	100m
Customs Number(Schedule B)	5902100000
Weight (imperial)	4.74
Weight (Metric)	21.5g/M
	Material Shortcut Flammability Halogenfree Operating Temperature REACH Compliant (Article 33) ROHS Compliant Package Quantity (Imperial) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial)