

181-24008



Article Number: 181-24008

Description: Slotted Cable & Wiring Duct, 2" x 4", Non-Adhesive, PVC, Gray, 120ft/carton

Base Data	Local Order Number	181-24008
	Type	SL2X4
	Color	Gray (GY)
	Features and Benefits	<ul style="list-style-type: none"> • Strong fingers prevent unwanted breaking. • Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. • Restricted opening design in the finger of the duct helps keep wires in place. • Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection
	Quantity Per	carton
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Technical Description	Non-Adhesive
	Short Description	Slotted Cable & Wiring Duct, 2" x 4", Non-Adhesive, PVC, Gray, 120ft/carton
	Product Dimensions	Length L (Imperial)
Length L (Metric)		1.83m
Width W (Imperial)		2.0"
Width W (Metric)		50.8mm
Width W2 (Imperial)		2.0"
Width W2 (Metric)		50.8mm
Width W3 (Imperial)		0.4"
Width W3 (Metric)		10.2mm
Width W4 (imperial)		1.0"
Width W4 (metric)		25.4mm
Width W5 (imperial)		3.6"

181-24008



Product Dimensions	Width W5 (metric)	91.4mm
	Width W6 (imperial)	0.5"
	Width W6 (metric)	12.7mm
	Height H (Imperial)	4.07"
	Height H (Metric)	103.4mm
	Mounting Hole Centers (Imperial)	4.0"
Material and Specifications		
	Material	Polyvinylchloride (PVC)
	Material Shortcut	PVC
	Flammability	self-extinguishing
	Operating Temperature	+122°F (+50°C)
	ROHS Compliant	Yes
	Certification/Specification	CSA
UL Recognized (US)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	120.0ft
	Package Quantity (Metric)	36.6m
	Customs Number(Schedule B)	3925900000