

596-00240

HellermannTyton

RATED AC OPERATING CURRENT	
MAX RATED AC OPERATING CURRENT	
RATED AC OPERATING VOLTAGE	
MAX RATED AC OPERATING VOLTAGE	
RATED SHORT CIRCUIT CURRENT	
MAXIMUM SYSTEM VOLTAGE	

Article Number: 596-00240

Description: Solar Label, Printable, 2017 Code, DC BACKUP SYSTEM, 4.0" x 2.0", PET, Red, 50/roll

Base Data	Local Order Number	596-00240
	Type	ACRATING
	Color	Red (RD)
	Features and Benefits	<ul style="list-style-type: none"> • Made with UV-stable inks and materials for durability and weather resistance. • Polyester is resistant to chemicals and solvents and will remain legible in dirty environments. • High abrasion and scuff resistance for high-performance labeling. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
	Quantity Per	reel
	Product Description	HellermannTyton printable Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Printable Solar Label, AC Ratings (Operating, Max Operating and Max System Current; Operating and Max Voltage) 4.0" X 2.0", Red
	Short Description	Solar Label, Printable, 2017 Code, DC BACKUP SYSTEM, 4.0" x 2.0", PET, Red, 50/roll
Product Dimensions	Width W (Imperial)	4.0"
	Width W (Metric)	101.6mm
	Height H (Imperial)	2.0"
	Height H (Metric)	50.8mm
	Material and Specifications	
Material	Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate	
Material Shortcut	840/926	
Adhesive	Acrylic	

596-00240



Material and Specifications	Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	NEC2011
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055