


Article Number: 596-00241



Description: Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 50/roll

| Base Data | |
|-----------------------|--|
| Local Order Number | 596-00241 |
| Type | DCRATING |
| Color | Red (RD) |
| Features and Benefits | <ul style="list-style-type: none"> • Made with UV-stable inks and materials for durability and weather resistance. • Polyester is resistant to chemicals and solvents and will remain legible in dirty environments. • High abrasion and scuff resistance for high-performance labeling. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. |
| Quantity Per | roll |
| Product Description | HellermannTyton printable Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed. |
| Technical Description | Printable Solar Label, DC Ratings (Operating Current, Voltage; Max Voltage; Short Circuit Current), 3.75" X 2.0", Red |
| Local Order Number 2 | Cross Reference = 10 per pack: 596-00851; Printable Metal Solar Placard 5 pack: 596-00864; Engravable Metal Solar Placard 5 pack: 596-00865 |
| Short Description | Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 50/roll |
| Product Dimensions | |
| Length L (Imperial) | 3.75" |
| Length L (Metric) | 92.25mm |
| Width W (Imperial) | 3.75" |
| Width W (Metric) | 92.25mm |
| Height H (Imperial) | 2.0" |
| Height H (Metric) | 50.8mm |

596-00241



| | | |
|-----------------------------|--------------------------------|---|
| Material and Specifications | | |
| | Material | Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate |
| | Material Shortcut | 840/926 |
| | Adhesive | Acrylic |
| | Adhesive Operating Temperature | -40°F to +180°F (-40°C to +82°C) |
| | Halogenfree | Yes |
| | Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| | ROHS Compliant | Yes |
| | Certification/Specification | IFC 2012 |
| | UL Recognized (US) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 50 |
| | Package Quantity (Metric) | 50 |
| | Customs Number(Schedule B) | 3919102055 |
| | Labels per Column | 1 |
| | Labels per Row | 1 |