

596-00246

# HellermannTyton

Article Number: 596-00246

Description: Solar Label, Reflective, SOLAR DISCONNECT, 6.5" x 1.0", VL, Red, 50/pkg

**SOLAR DISCONNECT**

Base Data	Local Order Number	596-00246
	Type	SOLARD
	Color	Red (RD)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Made with UV stable inks and materials for durability and weather resistance</li> <li>• Supplied with aggressive adhesive to ensure long life</li> <li>• Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections</li> <li>• Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers</li> </ul>
	Quantity Per	roll
	Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label, Reflective, "SOLAR DISCONNECT", 6.5" X 1", Red
	Local Order Number 2	Cross Reference = 10 per pack: 596-00674; Spanish version 50 per roll: 596-00810
	Short Description	Solar Label, Reflective, SOLAR DISCONNECT, 6.5" x 1.0", VL, Red, 50/pkg
Product Dimensions	Length L (Imperial)	6.5"
	Length L (Metric)	165.1mm
	Width W (Imperial)	6.5"
	Width W (Metric)	165.1mm
	Height H (Imperial)	1.0"
	Height H (Metric)	25.4mm
Material and Specifications	Material	Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

596-00246



Material and Specifications	Material Shortcut	242/552
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	NEC2011
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919905060
	Labels per Column	1
	Labels per Row	1