

596-00255

# HellermannTyton

Article Number: 596-00255

Description: Solar Label, Reflective, 2017 Code, MAIN PV AC DISCONNECT, 5.5" x 1.75", VL, Red, 50/roll

**MAIN PV SYSTEM  
AC DISCONNECT**

Base Data	Local Order Number	596-00255
	Type	MPVACDIS
	Color	Red (RD)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Made with UV stable inks and materials for durability and weather resistance.</li> <li>• The labels are supplied with aggressive adhesive to ensure long life.</li> <li>• Solar Installation labels meet NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li> </ul>
	Quantity Per	roll
	Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label, Reflective, "MAIN PV AC DISCONNECT", 5.5" X 1.75", Red
	Local Order Number 2	Cross Reference = 10 per pack: 596-00676; Metal Solar Placard 5 pack: 596-00861
	Short Description	Solar Label, Reflective, 2017 Code, MAIN PV AC DISCONNECT, 5.5" x 1.75", VL, Red, 50/roll
	Product Dimensions	Length L (Imperial)
Length L (Metric)		139.7mm
Width W (Imperial)		5.5"
Width W (Metric)		139.7mm
Height H (Imperial)		1.75"
Height H (Metric)		44.4mm
Material and Specifications		Material

596-00255



Material and Specifications	Material Shortcut	242/552
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	IFC 2012
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919905060
	Labels per Column	1
	Labels per Row	1